



Aussie Precast Products

The Rain Safe

Rainwater Collection and Reuse System

The Rain Safe allows collection of rainfall from the roof to be stored in ground or above ground to be reused in the household for normal non potable water use. The Rain Safe is of concrete construction made in accordance with AS 1546.1:1998. Specifications. There are two models available, **TRS 5T and TRS 10T**.

TRS 5T is a slimmer taller tank, capacity of 5000ltrs for either in ground or above ground use.
TRS 10T has a holding capacity of 10,000ltrs. In ground/above ground

SPECIFICATIONS:

Tanks

- manufactured in concrete with pedestrian lids.
- All tanks made to AS 1546.1:1998 specifications
- Tanks available in 5,000ltrs and 10,000ltrs.
- Tank recess key for concrete anchorage.
- All tanks have 100mm minimum air gap.

Pump: Claytech Rainsub 45 which is a submersible pump that is installed inside the rainwater tank. It has a built-in constant flow switch giving you pressure as soon as you turn on the tap. .

Other components included in the Rainsafe System are:

- Non-return Valve
- Mains top up float system
- First flush kit—volume calculated to roof area
- Mains pressure flow reducer
- Constant flow switch and mains top up float system conveniently located in concrete top box
- All components installed ready to be connected by plumber and electrician.

1300 739 337 (02) 64938327 Fax: (02) 64938338

info@aussieprecast.com.au

www.aussieprecast.com.au